

beautiful, quality, recommended,
creative, tasteful, the tough,
excellent, resistant

Swedish edition

*Glitsa American's newsletter
for flooring professionals*

© June 2002 Glitsa American, Inc.

Breathing Easy **Assuring Indoor Air Quality for Comfort and Health** by Duane Bartel (President)

Homeowners have good reason to be excited and pleased when they first observe their completed or recoated hardwood floors. The freshly coated surfaces beg the homeowner to “come on in”, set the furniture, hang the drapes and complete the finishing touches that define the space as home.

Unfortunately, contractors may miss a good opportunity to add value to this experience. That is in the area of assuring that the homeowner returns to a space that has good indoor air quality. Indoor air quality is a science in itself that focuses on two important matters – comfort and health.

All coatings emit vapors as they dry. Primarily, these vapors are evaporated solvents and their odors vary from mild to strong. One common misconception is that strong smelling solvents must be bad while solvents that do not have strong odors must be safe. Regardless of how much the vapors smell, the most comfortable and healthiest environment for the homeowner is achieved by aggressively expelling the vapors from the house. The homeowner will appreciate your concern for their comfort and well-being.

While leaving the house closed up and turning on the furnace or air conditioning will actively churn the air and quickly dilute the vapors throughout the house, it will not eliminate the vapors. Although it is quite possible that the vapors may be dispersed so evenly by this method that their smell will diminish to the limits of detection, the vapors will still be present. The best way to assure indoor air quality is by employing the following recommendations.

There is only one way to eliminate vapors effectively. That is to expel them from the house. This is achieved by exchanging the indoor air with clean outdoor air. Once a floor has dried to the touch, the vast majority of the solvents have been emitted. At this point, opening windows and doors is a good start. Using them in conjunction with the furnace (see cautions later in this article), ventilation or air conditioning systems helps immensely. Adding portable fans to the mix and turning on bathroom and kitchen exhaust fans will really stir things up. No fume can survive this kind of onslaught.

As long as outdoor air is actively being introduced to the house and there are no air spaces in the house where air is stagnant, such as closets, fumes will be eliminated after a



One common misconception is that strong smelling solvents must be bad while solvents that do not have strong odors must be safe.



sufficient number of air exchanges. How many is impossible to determine because of a multitude of factors that vary for every house and environment.

A house contains a fixed number of cubic feet of volume. If an equal volume (one air exchange) is brought in from outdoors, it will mix with the indoor air. For every volume of air entering the house, an equal amount must leave the house. The clean air mixes freely with the odor-filled air. There is no easy way to predict how much they will mix because so much depends on the way the air moves through the complex space comprising a typical house. How “tight” the house is and what “assist” is provided by mechanical air moving systems in the house (furnace, etc.) will greatly influence air exchange rates. Additionally, external factors such as wind blowing around the house and differences in temperature or even small differences in air pressure between the inside and the outside of the house can have a large impact on air exchange rates as well. All of these factors can be exploited to move air effectively and eliminate vapors. Each air exchange, each cycle, expels more of the vapors until at some point there are essentially no vapors or odors left to expel. Obviously, it would seem that the homeowner should want this to happen quickly as opposed to slowly. This means lots of air exchanges per hour is preferable to no exchanges or few exchanges per hour.

Another contributing factor influencing required air exchanges to clear the air is the amount of floor space being coated relative to the total square footage of the house. A two hundred square foot coating job in a two thousand square foot house will require considerably fewer air exchanges to clear the



Simply cracking open a window and opening an internal door can raise the rate of air exchange to approximately two per hour if another “exit” air path (cracked-open window) is provided as well.

primarily during the winter months when the need to ventilate and bring in outside air is directly at odds with the goal of maintaining acceptable levels of heat and not waste energy. The temptation is strong to leave the house closed up tight, run the furnace enough to maintain a moderate temperature, and wish the fumes away. Although this approach might actually work OK in older, less energy-efficient homes, because the “leakage” is high enough to actually achieve some acceptable air exchange rates, it will not work with new energy-efficient construction.

Contractors may actually consider reviewing their practices regarding ventilation requirements today as opposed to how they have dealt with these matters in the past. Houses today are built much tighter than in years past. A contractor who in the past never had to bother with ventilation after completing the final coat should be aware that the natural “leakiness” of older construction practices and standards pretty much assured good natural air exchange rates. That is not true today. Modern homes can easily attain a natural air exchange flow that is only a quarter of what older houses had. This means

recommendations for air exchange rates that result in comfortable and healthy living environments. For example, they recommend that during the heating season, a house should have air exchange rates of at least three per hour. However, it is quite possible with today’s energy efficient construction methods to achieve conditions as low as one-half of an air exchange per hour. On the other hand, the same room in an older, less energy-efficient house can easily have an air exchange rate of about two per hour even with the windows and doors closed. Obviously, though the older house has an energy disadvantage of “leaking in” cold air from outdoors, it has a health advantage of providing acceptable air exchange rates. This also allows the vapors to dissipate at a much higher rate. Likewise, bacteria, mold and other undesirable things have a tougher time staking a claim in this “breathing” environment. (See references 1,2,3 & 4).

Simply cracking open a window and opening an internal door for the “tight” construction example above can raise the rate of air exchange to approximately two per hour if another “exit” air path (cracked-open window) is provided as well. Adding a box fan in the window can bump the rate of air exchange to over 5 per hour. Although it is impossible to know how many air exchanges are required for a specific house to eliminate all the vapors, it is obvious that high rates of air exchange over a period of a couple of days has the potential to exchange outdoor air with indoor air hundreds of times. Unfortunately, sometimes a choice must be made during this brief ventilating period between saving energy or restoring indoor air quality. (See reference 1).

Sometimes the contractor can minimize the potential for lingering fumes, particularly

The temptation is strong to leave the house closed up tight, run the furnace enough to maintain a moderate temperature, and wish the fumes away.

air than would a floor-coating job covering every square foot of the house.

There is no doubt these goals are easier to achieve during warm seasons of the year. Obviously, cracking windows open, taking advantage of summer breezes, even setting up fans is generally no problem at those times. The dilemmas seem to appear

business as usual does not apply to the contractor’s responsibilities regarding ventilation. He must do more today than he did in the past to assure the homeowner occupies a space that is comfortable and safe to occupy.

NIOSH has done extensive studies to determine Indoor Air Quality standards and

in the winter, by making sure he is optimizing the coating process. It is vital that he follow the manufacturer's recommendations carefully. Allow stains to dry completely before coating. If a stain is not completely dry, it will slow down the cure time of subsequent coats, or worse – wrinkling or mottling could occur. All coatings should be applied at their recommended coverage rates and no heavier. Heavy coats take longer to dry, cure and expel all their solvents. Consequently, they will emit odors longer. Avoid coating at low temperatures. Coating at lower than recommended temperatures will extend the drying and curing times. (Safety tip: Depending on the type of coating used, it may necessary to heat up the house, then shut off the heat and any sources of ignition prior to coating).

In winter, in particular, the contractor would do well to educate the homeowner about the need for good ventilation during the first few days after the final coat is applied. He should alert the customer that there would be some heat energy loss in order to achieve the necessary ventilation. This can be a real dilemma for some people. Find out before you start the job if there is going to be an issue. It seems that there is a wide range of tolerance among consumers regarding the “comfort levels” they expect. Many homeowners consider residual vapors as a minor inconvenience and see no need to make a fuss about it. At the other extreme are small groups of people with various degrees of chemical sensitivities that are much more sensitive to residual vapors. Frequently, in those cases, most people cannot even detect an odor that the “sensitive” person finds unacceptable. For these reasons, it is a good idea to find out how they feel about wasting some heat energy for a couple of days in order to achieve excellent ventilation. Also ask them if they are chemically sensitive or if they are OK with temporarily living with some residual vapors for a few days. If they are very chemically sensitive or they object to wasting any heat

energy, they may be better off waiting until a warmer season to have this work done. Even people with chemical sensitivities should be able to enjoy hardwood floors so long as the coatings are applied properly, the curing conditions are suitable, aggressive ventilation is achieved and a sufficient time (determined by temperature and number of air exchanges) has elapsed before the homeowner returns and reoccupies the home.

Each contractor will develop methods that work best for him and his customers. For winter jobs, the key points are to maintain temperatures during the job according to the product application instructions. Ventilate, if possible, between coats once the coating

or portable fans may also be employed. The furnace's blower, acting as a fan (no heat) can often be utilized at this early phase of ventilating as long as the switch position on the thermostat has positions for “Fan Only”, the thermostat temperature selector has an “Off” range, and the pilot light has been extinguished. For additional information on safety measures regarding furnaces and appliance pilot lights, contact Glitsa Customer Service, 1-800-527-8111, for a copy of The Swedish Edition, March 2001 Edition which includes the article “Who Turned Out the Pilot Lights”.

Ideally, introducing outside air should tax the furnace enough to keep it running nearly

All coatings should be applied at their recommended coverage rates and no heavier. Heavy coats take longer to dry, cure and expel all their solvents.

is dry to the touch. Once the final coat has dried to the touch, crack open some windows just a little. Then, depending on the type of product used, when the fumes have subsided sufficiently to not present a fire hazard, set the furnace thermostat to about 70 degrees. Check back in a while to see what temperature the furnace is actually maintaining. As the coating dries, the windows can be opened a little more. The idea is to have a sufficient inflow of outside air to challenge the ability of the furnace to keep up without allowing the temperature to fall too much. Remember that the cold air will fall to the floor level so be careful to limit introducing really cold air. The goal is to introduce fresh air without harming the coating.

It is important to emphasize at this point the need to be very cautious regarding fire hazard when using the furnace after using solvent-borne coatings. Initial ventilation should not utilize the furnace. Initial air exchanges must be achieved by opening windows and doors to evacuate fumes. Once the fumes have subsided, exhaust fans and/

continuously, but not so much that the house temperature cannot be maintained above 60 degrees. Adjust this by increasing or decreasing the window openings, as long as the coating has cured sufficiently to handle the cold air at floor level. The reason for this is furnaces have powerful and efficient blowers coupled with efficient distribution ducting. Make good use of these assets. The blowers typically can move up to six hundred cubic feet per minute, fifteen to twenty percent of which is fresh outdoor air (assuming the furnace was installed properly). The ductwork distributes this air all over the house to flush out vapors. Each cubic foot of air moved carries away a portion of the vapors. It's like an invasion of clean air and, in the end, the clean air always wins. (See reference 5).

The use of portable fans and turning on kitchen and bathroom exhaust fans is very effective as well, as long as they are not used before the final coat is dry to the touch. Avoid using box fans in windows in cold weather. That could be a bit much. Cracking windows



The use of portable fans and turning on kitchen and bathroom exhaust fans is very effective as well, as long as they are not used before the final coat is dry to the touch.

open should be sufficient. Fans aimed into closets and into any place there is not much natural airflow is certainly recommended. In a room, it is best to use articulating fans and set them so that at one limit they aim at a corner, then sweep to the adjacent corner. If only a few fans are available, the best utilization is to place them in doorways blowing into a hallway. The “draw” of the fan will pull fumes evenly from all parts of the room. This will result in complete mixing of room air with no stagnant areas. (See reference 5).

In warmer seasons, it is equally important to achieve good rates of air exchange. Fans in rooms and box fans, particularly mounted in windows, can be very effective. The best way to take advantage of summer breezes to maximize air exchange may be to note the wind direction, then open the windows wide on the upwind and downwind sides of the house. Leave the side windows closed (using fans in these rooms). This way you not only take full advantage of the wind blowing into one side of the house, but the passage of the wind around the house will cause the air to speed up resulting in a slight drop in pressure on the downwind side of the house. This causes an area of low pressure (partial vacuum) immediately downwind of the house. So in addition to the wind being blown through the house, air is also being sucked through the house. The combined effect can result in a very respectable air exchange rate even when the wind is light. (See reference 4 & 5).

Back when houses were built without a large emphasis on energy efficiency, little was known about indoor air quality. It generally wasn't a problem. The birth of the science of indoor air quality was actually the result of some hard lessons learned from the consequences of building structures very “tight” to gain energy efficiency but not providing adequate ventilation. (See reference 5).

In 1981, a state building was completed called the Bateman building. At the time it was heralded as a model of energy efficiency. However, within a year of its opening it was unoccupied. Eighty percent of the occupants of one floor, for example, suffered from symptoms that were attributed to the building environment. It was ultimately concluded that poor ventilation was at fault. Since that time, in 446 episodes of “tight building syndrome” investigated by NIOSH, 52% were attributed to inadequate ventilation. Other minor contributors were air contamination from inside the building, air contamination from outside the building, microbiological contamination, and unknown causes. It can be argued that the contribution

of inadequate ventilation is, in fact, understated in these conclusions because if better ventilation had existed the other factors would have contributed even less. (See reference 3).

Undoubtedly, clean air is important to comfort and health. It is also relatively easy to achieve. It requires little effort to crack open some windows. It requires only a small additional effort to set up some fans. A few minutes of coaching a homeowner on how to make good use of their furnace and other systems to expel the fumes at an optimum rate is time well spent and will assure the homeowner you want them to be comfortable and healthy. Aggressive ventilation is key. Assuming the product has been applied correctly, optimizing air exchange rates should eliminate fumes and odors within a few days. Following these guidelines, a rule of thumb is if no odors remain the fumes are gone and the aggressive ventilating regimen can be stopped. Indoor air quality is defined as the quality of air within a living space that promotes comfort and health. Striving for that goal should give all of us a lot of comfort. ■

References:



1. National Paint and Coatings Association, PVA Emulsions Study by IT Corporation, Cincinnati, OH, 1992
2. NIOSH, Publication 98-123, PB 99,104,234, Building Air Quality: Action Plan.
3. The Dose Makes the Poison, M. Alice Ottoboni, John Wiley & Sons, Inc., 1997
4. 1997 Ashrae Handbook Fundamentals, I-P Edition, Ch. 25, Ventilation and Infiltration.
5. Modern Refrigeration and Air Conditioning, Althouse, Turnquist and Bracciano, The Goodheart-Willcox Company, Inc., 2000.